

Allied Telesis AT-x230-18GP-50 Gestito L2+ Gigabit Ethernet (10/100/1000) Supporto Power over Ethernet (PoE) Grigio



Marchio : Allied Telesis

Codice prodotto: 990-004132-50

Nome del prodotto : AT-x230-18GP-50

Allied Telesis AT-x230-18GP-50. Tipo interruttore: Gestito, Livello del commutatore: L2+. Tipo di porte RJ-45: Gigabit Ethernet (10/100/1000), Quantità di porte RJ-45: 16, Console port: RJ-45. Full duplex. Dimensioni tavola MAC: 16000 voci, Capacità di commutazione: 36,6 Gbit/s. Standard di rete: IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE....
Connettore di alimentazione: Jack DC-ingresso. Supporto Power over Ethernet (PoE). Montaggio rack

Management features		Protocols	
Switch type *	Managed	Management protocols	IGMP, MLD, Telnet, SMTP, NTP
Switch layer	L2+	Supported network protocols	SNTP
Quality of Service (QoS) support	✓	Design	
Web-based management	✓	Rack mounting *	✓
System event log	✓	Product colour	Grey
MIB support	RFC1212, RFC1213, RFC1227, RFC1239, RFC2011, RFC2012, RFC2013, RFC2096, RFC2819, RFC2863, RFC3418, RFC3621, RFC3636	LED indicators	✓
		Safety	UL60950-1, CAN/CSA-C22.2 No. 60950-1-03, EN60950-1, EN60825-1, AS/NZS 60950.1
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	16	Internal memory	256 MB
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Flash memory	64 MB
SFP module slots quantity	2	Power	
Console port	RJ-45	AC input voltage	100 - 240 V
Power connector	DC-in jack	AC input frequency	50 - 60 Hz
		Power consumption (max)	21 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.2, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✓
		Power over Ethernet (PoE) ports quantity	16
		Power over Ethernet plus (PoE+) ports quantity	8
10G support *	✗	Total Power over Ethernet (PoE) budget	296 W
Copper ethernet cabling technology	1000BASE-T, 100BASE-T, 10BASE-T	Operational conditions	
Port mirroring	✓	Operating temperature (T-T)	0 - 50 °C
Full duplex	✓	Storage temperature (T-T)	-20 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	5 - 90%
Link aggregation	✓	Storage relative humidity (H-H)	5 - 95%
Broadcast storm control	✓	Non-operating altitude	0 - 3048 m
Auto MDI/MDI-X	✓	Heat dissipation	168 BTU/h
Spanning tree protocol	✓	Weight & dimensions	
VLAN support	✓	Width	341 mm
Data transmission		Depth	231 mm
Switching capacity *	36.6 Gbit/s	Height	44 mm
Throughput	26.8 Mpps	Weight	3 kg
MAC address table *	16000 entries	Packaging data	
Jumbo frames support	✓	Package weight	4.2 kg
Packet buffer memory	1.5 MB	Certificates	
Security		Certification	UL, cUL, UL-EU
DHCP features	DHCPv6 client, DHCP client		
IGMP snooping	✓		

Security		Logistics data	
Security algorithms	EAP-TTLS, MD5, PEAP, SSL/TLS	Harmonized System (HS) code	85176990
Multicast features			
Multicast support	✓		



0767035202662



767035202662

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.