![BenQ logo]

# BenQ RP6504 lavagna interattiva 165,1 cm (65") 3840 x 2160 Pixel Touch screen Nero

Marchio : BenQ

Nome del prodotto : RP6504

Codice prodotto: 9H.F97TC.DE1

BenQ RP6504. Dimensioni diagonale schermo: 165,1 cm (65"), Area di lavorazione: 1428,5 x 803,5 mm, Luminosità schermo: 450 cd/m². Sistema operativo incluso: Android, Architettura processore: ARM Cortex A78 + ARM Cortex A55, Memoria utente: 64 GB. Potenza altoparlante: 20 W, Potenza RMS subwoofer: 16 W. Velocità trasferimento Ethernet LAN: 10,100,1000 Mbit/s. Connettore USB: USB tipo A, USB di tipo B, USB tipo-C, versione DisplayPort: 1.2a, Microfono: 3,5 mm

Display

Display diagonal *	165.1 cm (65")
Display brightness	450 cd/m²
Display resolution	3840 x 2160 pixels
Anti-glare screen	✔
HD type	4K Ultra HD
Panel type	IPS
Native aspect ratio	16:9
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	50000:1
Response time	8 ms
Touchscreen *	✔
Touch technology	Multi-touch
Touchscreen type	Infrared
Number of simultaneous touchpoints	50
Touch system response time	5 ms
Colour gamut	72%
Working area *	1428.5 x 803.5 mm
Surface material	Tempered glass
Low Blue Light technology	✔
Hardness	9H

Computer system

Operating system installed	Android
Operating system version	13
Built-in processor	✔
Processor architecture	ARM Cortex A78 + ARM Cortex A55
Processor cores	4
User memory	64 GB
RAM capacity	8 GB
Graphics card family	ARM
Graphics card	Mali-G57 MC5

Audio

Built-in speaker(s) *	✔
Number of built-in speakers	2
Speaker power	20 W
Built-in subwoofer	✔
Subwoofer RMS power	16 W
Built-in microphone	✔

Ports & interfaces

DisplayPort version	1.2a
DisplayPorts quantity	1
Ethernet LAN (RJ-45) ports	1
VGA (D-Sub) ports quantity	1
Line-in	✔
Line-out	✔
OPS slot	1
S/PDIF out port	✔
Microphone connectivity	3.5 mm
Headphone connectivity	3.5 mm
Audio output	3

Ergonomics

Product colour	Black
VESA mounting	✔
Panel mounting interface	600 x 400 mm
Wall mountable	✔

Performance

Humidity sensor	✔
Temperature sensor	✔
PM2.5 sensor	✔
Number of air ionizers	1
Motion sensor	✔

Power

Power consumption (typical)	95 W
Power consumption (standby)	0.5 W
AC input voltage	100-240 V
AC input frequency	50/60 Hz

System requirements

Security updates end date	30/11/2026

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	10 - 90%

Weight & dimensions

Network

Wi-Fi	✔
Bluetooth	✔
Bluetooth version	5.2
Ethernet LAN	✔
Ethernet LAN data rates	10,100,1000 Mbit/s
Near Field Communication (NFC)	✔

Ports & interfaces

USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	7
Interface module USB 3.2 Gen 1 (3.1 Gen 1) Type-B ports quantity	3
USB 2.0 ports quantity	1
USB connector type	USB Type-A, USB Type-B, USB Type-C
USB 2.0 Type-B Touch ports quantity	3
HDMI ports quantity	5
USB Type-C ports quantity	4
HDMI version	2.0
HDMI output ports quantity	1

Weight & dimensions

Width *	1488.4 mm
Depth	117.7 mm
Height *	937.6 mm
Weight	41 kg

Packaging data

Package width	210 mm
Package depth	1630 mm
Package height	1020 mm
Package weight	48 kg
Quantity per pack	1 pc(s)

Packaging content

Pen tray included	✔
Cables included	HDMI, Power, USB, USB Type-C, VGA
Remote control included	✔
Mounting kit	✔
Stylus included	✔
Number of stylus pens	2

Other features

Country of origin	China

Logistics data

Customs product code (TARIC)	8528521000
Products per pallet	5 pc(s)

||||||||||||||||||||||||||

4718755092459

||||||||||||||||||||||||||

8717472600295

||||||||||||||||||||||||||

0840046049133

||||||||||||||||||||||||||

840046049133