




LG 22SM3G-B Pannello piatto per segnaletica digitale 54,6 cm (21.5") Wi-Fi 250 cd/m² UHD+ Nero 16/7

Marchio : LG

Codice prodotto: 22SM3G-B.AEU

Nome del prodotto : 22SM3G-B



LG 22SM3G-B. Design del prodotto: Pannello piatto per segnaletica digitale. Dimensioni diagonale schermo: 54,6 cm (21.5"), Risoluzione del display: 1920 x 1080 Pixel, Luminosità schermo: 250 cd/m², Tipologia HD: UHD+. Wi-Fi. Ore di servizio (ore/giorni): 16/7. Colore del prodotto: Nero

Display		Design	
Panel type	IPS	Bezel width (bottom)	1.63 cm
LED backlighting type	Edge-LED	Bezel width (side)	1.63 cm
Display diagonal *	54.6 cm (21.5")	Bezel width (top)	1.63 cm
Display resolution *	1920 x 1080 pixels	Performance	
Display brightness *	250 cd/m ²	Purpose *	Universal
HD type *	UHD+	Operating hours (hours/days)	16/7
Touchscreen *	✗	Power	
Response time	14 ms	Power consumption (typical) *	30 W
Contrast ratio (typical)	1000:1	Power consumption (standby) *	15 W
Contrast ratio (dynamic)	400000:1	AC input voltage	100 - 240 V
Viewing angle, horizontal	178°	AC input frequency	50 - 60 Hz
Viewing angle, vertical	178°	Computer system	
Display number of colours	16.78 million colours	Internal memory	8 GB
Native refresh rate	60 Hz	Weight & dimensions	
Haze rate	25%	Display width	510.3 mm
Ports & interfaces		Display depth	53.8 mm
HDMI ports quantity *	2	Display height	302.1 mm
HDMI version	2.2	Display weight	3.34 kg
USB port *	✓	Width	510.3 mm
USB ports quantity	1	Depth	53.8 mm
USB version	2.0	Height	302.1 mm
Ethernet LAN *	✓	Weight	3.34 kg
Ethernet LAN (RJ-45) ports	1	Packaging data	
Wi-Fi *	✓	Package width	565 mm
Audio (L/R) in	1	Package depth	103 mm
RS-232C	✓	Package height	357 mm
Remote (IR) input	1	Package weight	4.74 kg
OPS module slot	✗	Packaging content	
Audio		Remote control included	✓
Built-in speaker(s) *	✓	Cables included	AC, HDMI
Number of built-in speakers	2	Operational conditions	
RMS rated power	2 W	Operating temperature (T-T)	0 - 40 °C
Design			
Product design *	Digital signage flat panel		

Design		Operational conditions	
Placement supported *	Indoor	Operating relative humidity (H-H)	10 - 80%
Orientation	Horizontal	Certificates	
Product colour *	Black	Certification	CB / NRTL FCC Class "A" / CE
VESA mounting *	✓	Logistics data	
Panel mounting interface	100 x 100 mm	Harmonized System (HS) code	85285210
Technical details		Sustainability certificates	ErP

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 13-MAR-2025. Prints or copies of Information are only valid on the printed Publication date